

# LIFT TABLES

2,000 / 3,000 / 4,000 / 5,000 / 6,000 LBS



## SPECIFICATIONS

### STANDARD 24" WIDE BASE LIFT TABLES

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W X L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	RAISED HT (IN.)	UP SPEED (SEC.)	MOTOR (H.P.)	VOLT/HP/HZ	SHIP WEIGHT (LBS)
<b>24" TRAVEL - 24" WIDE x 36" LONG PLATFORM/BASE</b>									
SL24-20	2,000	24 x 36	48 x 60	9	33	15	1	115/1/60	450
SL24-40	4,000	24 x 36	48 x 60	9	33	21	1	115/1/60	470
SL24-60	6,000	24 x 36	48 x 60	9	33	32	1	115/1/60	520
<b>36" TRAVEL - 24" WIDE x 48" LONG PLATFORM/BASE</b>									
SL36-20	2,000	24 x 48	48 x 72	9	45	20	1	115/1/60	600
SL36-30	3,000	24 x 48	48 x 72	9	45	30	1	115/1/60	620
SL36-40	4,000	24 x 48	48 x 72	9	45	37	1	115/1/60	650
SL36-50	5,000	24 x 48	48 x 72	9	45	40	1	208, 220, 460, 575/3/60	680
SL36-60	6,000	24 x 48	48 x 72	9	45	48	1	208, 220, 460, 575/3/60	700
<b>42" TRAVEL - 24" WIDE x 60" LONG PLATFORM/BASE</b>									
SL42-20	2,000	24 x 60	48 x 84	9	51	25	1	115/1/60	625
SL42-40	4,000	24 x 60	48 x 84	9	51	47	1	115/1/60	800
SL42-60	6,000	24 x 60	48 x 84	9	51	50	1	208, 220, 460, 575/3/60	950
<b>48" TRAVEL - 24" WIDE x 72" LONG PLATFORM/BASE</b>									
SL48-20	2,000	24 x 72	48 x 96	9	57	32	1	115/1/60	800
SL48-40	4,000	24 x 72	48 x 96	9	57	50	1	115/1/60	950
SL48-60	6,000	24 x 72	48 x 96	9	57	56	1	208, 220, 460, 575/3/60	1,200

**SPECIFICATIONS** - wide based units; for wider platform applications and greater stability.

### 36" WIDE BASE LIFT TABLES

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W X L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	RAISED HT (IN.)	UP SPEED (SEC.)	MOTOR (H.P.)	VOLT/HP/HZ	SHIP WEIGHT (LBS)
<b>24" TRAVEL - 36" WIDE x 36" LONG PLATFORM/BASE</b>									
3SL24-20	2,000	36 x 36	60 x 60	9	33	15	1	115/1/60	480
3SL24-40	4,000	36 x 36	60 x 60	9	33	21	1	115/1/60	520
3SL24-60	6,000	36 x 36	60 x 60	9	33	32	1	115/1/60	550
<b>36" TRAVEL - 36" WIDE x 48" LONG PLATFORM/BASE</b>									
3SL36-20	2,000	36 x 48	60 x 72	9	45	20	1	115/1/60	750
3SL36-40	4,000	36 x 48	60 x 72	9	45	38	1	115/1/60	790
3SL36-60	6,000	36 x 48	60 x 72	9	45	48	1	208, 220, 460, 575/3/60	850
<b>42" TRAVEL - 36" WIDE x 60" LONG PLATFORM/BASE</b>									
3SL42-20	2,000	36 x 60	60 x 84	9	51	25	1	115/1/60	830
3SL42-40	4,000	36 x 60	60 x 84	9	51	47	1	115/1/60	890
3SL42-60	6,000	36 x 60	60 x 84	9	51	50	1	208, 220, 460, 575/3/60	950
<b>48" TRAVEL - 36" WIDE x 72" LONG PLATFORM/BASE</b>									
3SL48-20	2,000	36 x 72	60 x 96	9	57	32	1	115/1/60	1,100
3SL48-40	4,000	36 x 72	60 x 96	9	57	50	1	115/1/60	1,200
3SL48-60	6,000	36 x 72	60 x 96	9	57	56	1	208, 220, 460, 575/3/60	1,280

### 48" WIDE BASE LIFT TABLES

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W X L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	RAISED HT (IN.)	UP SPEED (SEC.)	MOTOR (H.P.)	VOLT/HP/HZ	SHIP WEIGHT (LBS)
<b>24" TRAVEL - 48" WIDE x 36" LONG PLATFORM/BASE</b>									
4SL24-20	2,000	48 x 36	72 x 60	9	33	15	1	115/1/60	700
4SL24-40	4,000	48 x 36	72 x 60	9	33	24	1	115/1/60	740
4SL24-60	6,000	48 x 36	72 x 60	9	33	34	1	115/1/60	780
<b>36" TRAVEL - 48" WIDE x 48" LONG PLATFORM/BASE</b>									
4SL36-20	2,000	48 x 48	72 x 72	9	45	20	1	115/1/60	840
4SL36-40	4,000	48 x 48	72 x 72	9	45	38	1	115/1/60	890
4SL36-60	6,000	48 x 48	72 x 72	9	45	48	1	208, 220, 460, 575/3/60	950
<b>42" TRAVEL - 48" WIDE x 60" LONG PLATFORM/BASE</b>									
4SL42-20	2,000	48 x 60	72 x 84	9	51	26	1	115/1/60	890
4SL42-40	4,000	48 x 60	72 x 84	9	51	42	1	115/1/60	950
4SL42-60	6,000	48 x 60	72 x 84	9	51	50	1	208, 220, 460, 575/3/60	1,000
<b>48" TRAVEL - 48" WIDE x 72" LONG PLATFORM/BASE</b>									
4SL48-20	2,000	48 x 72	72 x 96	9	57	32	1	115/1/60	950
4SL48-40	4,000	48 x 72	72 x 96	9	57	50	1	115/1/60	1,100
4SL48-60	6,000	48 x 72	72 x 96	9	57	56	1	208, 220, 460, 575/3/60	1,200

See page 9 for options available.

## CAPACITY

- 2,000/3,000/4,000/5,000/6,000 lbs.

## PLATFORM SIZES

- 24" wide x 36" long to 72" wide x 96" long

## BASE SIZES

- Standard 24", 36", 48" wide x 36", 48", 60", 72" long

## TRAVEL

- 24", 36", 42", 48" vertical travel

## LOWERED HEIGHT

- 9" (special heights available)

## SAFETY

- Velocity fuse is standard on each cylinder
- Heavy duty hydraulic cylinders - chrome plated rod with polyurethane seals

## POWER SUPPLIES

A/C 110/1/60 volt (standard)

Hand or foot operated

A/C 460/575/3/60 volt (opt.)

Hand or foot operated

Air/Hydraulic

Foot operated (standard)

Hand operated (optional)

- Internally mounted
- Easily accessible for maintenance or repair
- Motors - Single phase 1 h.p. and three phase 1-1/2 h.p. - hand or foot operated standard

## MAINTENANCE

- Hinged table top provides easy access to power unit and cylinders
- Self lubricated bronze bushings on all wear points

## OPTIONS

- Oversized platforms
- Beveled edges for pit mounting
- Eye-bolts for pit mounting
- Rotating tops
  - spring detents
  - manual detents
- Roller conveyor, Ball transfer tops
- Bellow safety skirting
- Safety tape switch
- Safety touch bars
- Semi-portable
- Portable
- Tandem lifts
- Double scissor lifts

# LIFT TABLES

2,000 / 3,000 / 4,000 / 5,000 / 6,000 LBS



## OPTIONS

Manual Detent  
(Spring loaded also available)

Rotating Top

Ball Transfer Top

WIDE BASE LIFT TABLE

Oversize Checker Board Top

Roller Conveyor Top

Bellow Safety Skirting

Beveled Edge for Pit Mounted Applications

TANDEM LIFT

PORTABLE LIFT/WORK PLATFORM

SELF PROPELLED LIFT TABLE

Step up

UMHW Positioning Jig

Hand Railing

Portable Dolly Handle

4 Casters, (two swivel, two fixed)

Heavy Duty Floor Lock

Two Wheels at other end

Flip Down Platform

LOADING DOCK APPLICATION

SEMI-PORTABLE OPTION

PORTABLE OPTION